


## PRODUCT MATRIX FOR: FDXXYY

Product Number	Spectral Wavelength	Optional Power Compatibility	Alternative Connector
FD XX YY - "H" "W" # in inches**  # indicates cable exit side	(blue) 470 (green) 520 (red) 660 (infra-red) 880 (white) WHI	IC <sup>c</sup> C2 C3 C5 24	M12* (male)

### Specifications

- Expandable Flat Diffuse Light
- Max Length: 22" x 34" (589mm x 864mm)
- Cable exits "Y" side
- Aperture Odd: 0.88" (22mm)
- Aperture Even: 1.75" (46mm)



[Link to drawings](#)

[Odd/Odd Dimensions](#)

[Even/Even Dimensions](#)

IC = iCS (requires 24v power supply)

C2 = Ai Connector

C3 = Pulsar 710 Connector

C5 = Pulsar 320 Connector

<sup>c</sup> Available on 660 & 880 lights up to 50 sq. inches; and greater than 6 sq. inches, up to 50 sq. inches for WHI, 470 & 520 lights

\* Available w/ IC and 24v options only

\*\* Lights must be ordered w/ either odd/odd or even/even dimensions.

**Built-to-order lights are non-returnable**

**Lights w/ a surface area of greater than 16 square inches requires either 24v wiring or the use of the Pulsar 710.**

# EXPANDABLE



800-594-2121 · [www.ksetexas.com](http://www.ksetexas.com)